



触摸屏控制和APP控制 (支持安卓和苹果系统)



打开方便，易于维护



可选件：打印机

- 卓越设计、结构紧凑、操控简单；
- 大型真空内腔；包装盖由厚实的有机玻璃制成；
- 封装杆方便拆卸；
- 触摸屏控制；
- 带0.1秒等级的密封、抽真空和气体的时间设置；
- 可显示真空的百分比和剩余时间；
- 可存贮 10 项程序；
- 可根据包装的产品不同而设置相应的自动程序；
- 需更换油的信号提示；
- 表面平整，清洁非常方便；
- 内置可识别手机 APP 的 Wi-Fi 装置；
- 每台机器标配配有包装液体用树脂板；
- 落地式真空包装机 W8 70 TOP 需提前预订。

- Premium materials body construction
- AISI 304 thick stainless steel vacuum chamber counter
- Automatic lid lifting system
- Easily removable sealing bar
- Intuitive touch screen display
- Flat-top design with wide chamber
- Extremely easy cleaning operations
- Fully automatic sensor mode, with dedicated liquid and marinade programs
- User customisable programs (10)
- Intuitive vacuum and sealing time controls
- Build-in maintenance management system
- Oil-change and filter-change alert system
- Preheating and oil-cleaning function
- Total cycle and total pump usage counter
- Build-in Wi-Fi connectivity with dedicated phone APP
- External vacuum mode (accessories needed)

## 可选件





- 外接抽真空的容器和软管；
- 自动换油装置；
- 可打印包装日期和时间的打印机。

## Available accessories:

- Thermal label printer
- External vacuum hose and reinforced GN containers and lids
- AOR automatic oil replacement system available (on-demand)



W8 70 TOP



产品型号	功率	电源	真空泵	密封条	内腔尺寸	A	B	C	D	E	F	G	H	净重	包装尺寸	毛重
	KW		mc/h	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	mm	kg
W8 30 TOP	0.35	230V / 50Hz 单相	8	310	340 x 360 x 160	402	525	408	587	334	340	95	170	38	720 x 570 x 770	48
W8 40 TOP	0.75	230V / 50Hz 单相	21	410	430 x 410 x 170	493	585	422	630	390	430	99	180	56	760 x 640 x 770	66
W8 40 TOP AOR	0.75	230V / 50Hz 单相	21	410	430 x 410 x 170	493	585	422	630	390	430	99	180	56	760 x 640 x 770	66
W8 50 TOP	0.75	230V / 50Hz 单相	21	510	545 x 460 x 190	609	640	420	605	430	540	90	210	70	840 x 870 x 750	86
W8 50 DB TOP	0.75	230V / 50Hz 单相	21	410 x 2	545 x 460 x 190	609	640	420	605	424	428	90	210	75	840 x 870 x 750	87
W8 70 TOP	1.1	400V / 50Hz 三相	40	640 x 1 410 x 2	780 x 490 x 190	877	674	1134	1368	424	660	95	200	167	1200 x 800 x 1350	180